

ALGORITHMS FOR CONSTRUCTION OF OPTIMAL AND
SUBOPTIMAL SOLUTIONS IN NETWORK
OPTIMIZATION PROBLEMS

L.A. Pilipchuk¹, A.S. Pilipchuk², Y.H. Pesheva³ §

¹Belarussian State University
4, Nezalezhnosti Ave., Minsk, 220050, BELARUS
e-mail: pilipchuk@bsu.by

²State Scientific Institution
99, Academician A.K. Krasin Str., Minsk, 220109, BELARUS
e-mail: pilip74@rambler.ru

³Department of Differential Equations
Faculty of Applied Mathematics and Informatics
Technical University of Sofia
P.O. Box 384, Sofia, 1000, BULGARIA
e-mail: yhp@vmei.acad.bg

Abstract: For a distributive flow programming optimization problem of a special structure direct and dual algorithms are constructed. These algorithms are based on a research of the theoretical and graph properties of the solution space bases. Optimality conditions are received, that allow to calculate a part of the components of the Lagrange vector. Algorithms that decompose calculation systems for pseudo-plans of the problem are presented. Suitable directions for change of the dual criterion function are constructed.

AMS Subject Classification: 05C50, 15A03, 15A06, 65K05, 90C08, 90C35

Key Words: sparse linear system, underdetermined system, direct method, dual method, basis of a solution space of a homogeneous linear system, decomposition of a system, network, network support, spanning tree, fundamental system of cycles, characteristic vector, optimality and suboptimality plan, pseudo-plan

Received: October 10, 2008

© 2009 Academic Publications

§Correspondence author

1. Introduction

Many problems in linear and nonlinear programming [2], [1] have in details developed theory and comprehensively investigated methods of solution. However the process of allocation of special problems in separate classes [3] and the development of new solution methods for them is a problem of interest. It is connected with the fact that each class of problems is characterized by a special structure of the set of parameters and restrictions. The investigated problem concerns the class of network optimization problems and has additional parameters, such as the variables of intensity of units, transformation factors of an arc flow (the generalized network), interrelation of the plan components (additional restrictions). Application to the solution of network optimization problems of special algorithms which take into account features of a problem, its theoretical and graph properties [3], [8], modern achievements in numerical realization of flow programming problems allows to solve high dimensional problems.

2. Statement of the Problem, Basic Concepts and Definitions

Consider the following mathematical model of an extreme network problem

$$\varphi(x) = \sum_{(i,j) \in U} c_{ij}x_{ij} + \sum_{j \in I^*} c_j x_j \longrightarrow \min, \quad (1)$$

$$\sum_{(i,j) \in I_i^+(U)} x_{ij} - \sum_{(i,j) \in I_i^-(U)} \mu_{ji}x_{ji} = \begin{cases} x_i \text{sign}(i), & i \in I^*, \\ a_i, & i \in I \setminus I^*, \end{cases} \quad (2)$$

$$\sum_{(i,j) \in U} \lambda_{ij}^p x_{ij} + \sum_{i \in I^*} \lambda_i^p x_i = \beta^p, \quad p = \overline{1, q}, \quad (3)$$

$$0 \leq x_{ij} \leq d_{ij}, \quad (i, j) \in U, \quad (4)$$

$$b_{*i} \leq x_i \leq b_i^*, \quad i \in I^*, \quad (5)$$

where $G = (I, U)$ – a finite orientated generalized network without multiple arcs and loops with set of nodes I and set of arcs U , $|U| \gg |I|$, $I_i^+(U) = \{j : (i, j) \in U\}$, $I_i^-(U) = \{j : (i, j) \in U\}$, x_{ij} – a flow along the arc (i, j) ; μ_{ij} – transformation factor of the flow along arc (i, j) , $\mu_{ij} \in [0, 1]$, I^* – a subset of I , $I^* \neq \emptyset$. Nodes $i \in I^*$ are named dynamic, $\text{sign}(i) = 1$, if $i \in I_+^*$; $\text{sign}(i) = -1$, if $i \in I_-^*$; $I_+^*, I_-^* \subseteq I^*$, $I_+^* \cap I_-^* = \emptyset$

Any node is a point of production (or consumption) of some item, x_{ij} – a

flow on arc $(i, j), \mu_{ij}$ – factor of transportation losses of goods from node i to node j on arc $(i, j), I^*$ – set of nodespoints of manufacture (consumption) with a preliminary unknown volume x_i of the manufactured (consumed) goods, a_i – volume of production (consumption) at node $i \in I \setminus I^*$.

Vector $x = (x_{ij}, (ij) \in U, x_i, i \in I^*)$ – is a plan, if on it restrictions (2)-(5) of the problem are carried out. A plan $x^0 \in X$ is optimal, if $c'x^0 = \min c'x, x \in X$, where X is the set of plans. If $\varepsilon \geq 0$, a suboptimal (ε -optimal) plan x^ε is defined by an inequality

$$c'x^\varepsilon - c'x^0 \leq \varepsilon, \quad x^\varepsilon \in X.$$

We shall name restrictions (2) a network part of system of basic restrictions (2), (3), restrictions (3) – additional basic restrictions, restrictions (4), (5) – direct restrictions.

3. A Network Part of the System of Basic Restrictions, Support Criterion

Let us define a support of a network $G = (I, U)$ for system (2).

Definition 1. The set of sets $R = \{U_R, I_R^*\}, U_R \subseteq U, I_R^* \subseteq I^*$ is named a support of a network $G = (I, U)$ for system (2), if at $\tilde{U}_R = U_R, \tilde{I}_R^* = I_R^*$ system

$$\sum_{j \in I_i^+(\tilde{U}_R)} x_{ij} - \sum_{j \in I_i^-(\tilde{U}_R)} \mu_{ji}x_{ji} = \begin{cases} x_i \text{sign}(i), i \in \tilde{I}_R^*, \\ 0, i \in I \setminus \tilde{I}_R^* \end{cases} \quad (6)$$

has only a zero solution, and has a nonzero solution in each of the following cases:

- 1) $\tilde{U}_R = U_R \cup (i, j), \tilde{I}_R^* = I_R^*$, for any arc $(i, j) \in U \setminus U_R$;
- 2) $\tilde{U}_R = U_R, \tilde{I}_R^* = I_R^* \cup \{i\}$, for any node $i \in I^* \setminus I_R^*$.

Theorem 1. (Network Support Criterion) *The set of sets $R = \{U_R, I_R^*\}$ is a support of a network $G = (I, U)$ for system (2), if and only if the following conditions are fulfilled:*

- 1) $|U_R| + |I_R^*| = |I|$;

2) any component of the connectivity $G_R^l = \{I^l, U_R^l\}, I^l = I(U_R^l), l = \overline{1, s}$, (s -number of the components of connectivity) of the network $G_R = (I, U_R)$ is a network of one of the following types:

- a) does not contain cycles (is a tree), and contains a unique node from set $I_R^l, |I_R^l \cap I_R^*| = 1$;

b) Contains a unique nondegenerate cycle and does not contain nodes from set I^* , $I_R^l \cap I_R^* = \emptyset$; $l = \overline{1, s}$.

Proof of Theorem 1 is given in [5].

Definition 2. A cycle is called nonsingular (nondegenerate), if the product of transformation factors of arc flows for its forward arcs is not equal to the product of factors of transformation of arc flows for its backward arcs.

4. Fundamental System of Elements

On the basis of Theorem 1 we shall choose a support $R = \{U_R, I_R^*\}$ of network G for system (2). Consider the construction of the generated characteristic vectors [8], which make fundamental system of solutions of system (7):

$$\sum_{j \in I_i^+(U)} x_{ij} - \sum_{j \in I_i^-(U)} \mu_{ji} x_{ji} = \begin{cases} x_i \text{sign}[i], & i \in I^*, \\ 0, & i \in I \setminus I^*. \end{cases} \quad (7)$$

The theoretical and graph structure of support $R = \{U_R, I_R^*\}$ of network G for the network part of system of basic restrictions (2) is a set of s – components of connectivity

$$G^l = (I^l, U_R^l), \bigcup_{l=1}^s I^l = I, I^l = I(U_R^l), \quad l = \overline{1, s} \quad I_R^* = \bigcup_{l=1}^s I_R^l,$$

each of which is either a tree containing a unique dynamic node from set $i \in I_R^*$, $|I_R^l \cap I^l| = 1$, or does not contain dynamic nodes $I_R^l \cap I^l = \emptyset$ and contains a unique nondegenerate cycle. On the basis of network properties of the support (Theorem 1) theoretical and graph properties of the fundamental system of solutions of system (7) are considered in work [8] and the general solution of linear system (2) is constructed. We shall designate through $\delta_{\tau\rho} = (\delta_{ij}^{\tau\rho}, (i, j) \in U; \delta_i^{\tau\rho}, i \in I^*)$ and $\delta_\gamma = (\delta_{ij}^\gamma, (i, j) \in U; \delta_i^\gamma, i \in I^*)$ the characteristic vectors generated by arcs $(\tau, \rho), (\tau, \rho) \in U \setminus U_R$, and nodes $\gamma, \gamma \in I^* \setminus I_R^*$ accordingly, making fundamental system of solutions of system (7), see [8], [6].

Consider the graph $\tilde{G} = (I, U_R \cup (\tau, \rho)), (\tau, \rho) \in U \setminus U_R, I_R^* \subseteq I$, where set of sets $R = \{U_R, I_R^*\}$ forms a support of network $G = (I, U)$ for system (2). Among the components of connectivity of network $\tilde{G} = (I, U_R \cup (\tau, \rho))$ there is a unique component of connectivity (we shall designate it) which is a network of one of the following types:

a) contains a unique nondegenerate cycle and a unique node from set I_R^* , $|I^l \cap I_R^*| = 1$;

b) contains a circuit connecting two nodes from set I_R^* , $|I_R^l \cap I_R^*| = 2$;

c) contains two cycles, at least one of which is non degenerate, and does not contain nodes from set I_R^* , $|I_R^l \cap I_R^*| = \emptyset$.

Theorem 2. Among the components of the characteristic vector $\delta_{\tau\rho}$ generated by arc $(\tau, \rho) \in U \setminus U_R$ or components of the characteristic vector δ_γ generated by node $\gamma \in I^* \setminus I_R^*$, nonzero can be only those components of the specified vectors which correspond to elements (arcs and dynamic nodes) of sets $U_R \cup (\tau, \rho)$ and I_R^* and belong to the following network structures:

a) the unique circuit connecting a dynamic node (we shall designate it u) from set I_R^* and a node v of a cycle;

b) the unique circuit connecting nodes u and v from set I_R^* ;

c) two cycles and a unique circuit which connects nodes of the specified cycles.

The proof of the theorem is given in [8].

5. Decomposition of System of Restrictions

Theorem 3. The general solution of system (2) can be presented [8] in the following form:

$$\begin{aligned} x_{ij} &= \sum_{(\tau, \rho) \in U \setminus U_R} x_{\tau\rho} \delta_{ij}^{\tau\rho} + \sum_{\gamma \in I^* \setminus I_R^*} x_\gamma \delta_{ij}^\gamma + \tilde{x}_{ij}, (i, j) \in U_R, \\ x_i &= \sum_{(\tau, \rho) \in U \setminus U_R} x_{\tau\rho} \delta_i^{\tau\rho} + \sum_{\gamma \in I^* \setminus I_R^*} x_\gamma \delta_i^\gamma + \tilde{x}_i, i \in I_R^*, \end{aligned} \quad (8)$$

where $\tilde{x} = (\tilde{x}_{ij}, (i, j) \in U; \tilde{x}_i, i \in I^*)$ – any particular solution of system (2).

Theorem 4. (Network Support Criterion) The aggregation of sets $K = \{U_K, I_K^*\}$ is a support of a network $G = (I, U)$ for system (2), (3) if and only if the following conditions are executed:

1) The aggregation of sets $K = \{U_K, I_K^*\}$ can be presented as an association of not intersecting sets of sets $R = \{U_R, I_R^*\}$, $W = \{U_W, I_W^*\}$ and $U_K = U_R \cup U_W$, $U_R \cap U_W = \emptyset$, $I_K^* = I_R^* \cup I_W^*$, $I_R^* \cap I_W^* = \emptyset$;

2) The aggregation of sets $R = \{U_R, I_R^*\}$ – is a support of the network $G = (I, U)$ for system (2) (Theorem 1).

3) $|W| = q$, where q – the number of linearly independent equations of system (3).

4) The matrix of determinants $\Lambda_W = (\Lambda_{W_1}, \Lambda_{W_2})$, is nonsingular,

$$\Lambda_{\tau\rho}^p = \sum_{(i,j) \in U_R} \lambda_{ij}^p \delta_{ij}^{\tau\rho} + \sum_{i \in I_R^*} \lambda_i^p \delta_i^{\tau\rho} + \lambda_{\tau\rho}^p,$$

$$\Lambda_{W_1} = (\Lambda_{\tau\rho}^p, p = \overline{1, q}; (\tau, \rho) \in U_W), \quad \Lambda_{W_2} = (\Lambda_{\gamma}^p, p = \overline{1, q}; \gamma \in I_W^*),$$

$$\Lambda_{\gamma}^p = \sum_{(i,j) \in U_R} \lambda_{ij}^p \delta_{ij}^{\gamma} + \sum_{i \in I_R^*} \lambda_i^p \delta_i^{\gamma} + \lambda_{\gamma}^p.$$

On the basis of Theorem 4 we execute decomposition of system (2), (3):

$$\sum_{(\tau, \rho) \in U \setminus U_R} \Lambda_{\tau\rho}^p x_{\tau\rho} + \sum_{\gamma \in I^* \setminus I_R^*} \Lambda_{\gamma}^p x_{\gamma} = \tilde{\beta}^p, \quad p = \overline{1, q}, \quad (9)$$

$$\tilde{\beta}^p = \beta^p - \sum_{(i,j) \in U_R} \lambda_{ij}^p \tilde{x}_{ij} - \sum_{(k) \in U_R} \lambda_k^p \tilde{x}_k;$$

$$\Lambda_{\tau\rho}^p = \sum_{(i,j) \in U_R} \lambda_{ij}^p \delta_{ij}^{\tau\rho} + \sum_{i \in I_R^*} \lambda_i^p \delta_i^{\tau\rho} + \lambda_{\tau\rho}^p, \quad (10)$$

$$\Lambda_{\gamma}^p = \sum_{(i,j) \in U_R} \lambda_{ij}^p \delta_{ij}^{\gamma} + \sum_{i \in I_R^*} \lambda_i^p \delta_i^{\gamma} + \lambda_{\gamma}^p.$$

We shall name quantities $\Lambda_{\tau\rho}^p$, Λ_{γ}^p determinants of the network structures making fundamental system of solutions of system (7). They are generated by arcs $(\tau, \rho) \in U \setminus U_R$ and nodes $\gamma \in I^* \setminus I_R^*$ accordingly, corresponding to the p -th restriction of system of additional restrictions (3), $p = \overline{1, q}$.

Consider variables corresponding to aggregation of sets W . The system (9) will become

$$\Lambda_W x_W = \tilde{\beta} - \Lambda_N x_N, \quad (11)$$

$$x_W = (x_{\tau\rho}, (\tau, \rho) \in U_W; x_{\gamma}, \gamma \in I_W^*),$$

$$x_N = (x_{\tau\rho}, (\tau, \rho) \in U_N; x_{\gamma}, \gamma \in I_N^*).$$

The system (11) has a unique solution due to nonsingularity of the matrix Λ_W .

The support components are calculated according to (8).

6. Increment of the Objective Function

Pair $\{x, K\}$ of a plan and a support is called a support plan. Support plan $\{x, K\}$ is nonsingular if it satisfies the following conditions:

$$0 < x_{ij} < d_{ij}, \quad (i, j) \in U_K; \quad a_{*i} < x_i < a_i^*, \quad i \in I_K^*. \quad (12)$$

Alongside with plan x we consider plan \bar{x} , $\Delta x = \bar{x} - x$. From [8], [7] it follows that for the increment $\Delta x = (\Delta x_{ij}, (i, j) \in U; \Delta x_i, i \in I^*)$ the following relations are carried out:

$$\begin{aligned} \Delta x_{ij} &= \sum_{(\tau, \rho) \in U \setminus U_R} \delta_{ij}^{\tau\rho} \Delta x_{\tau\rho} + \sum_{\gamma \in I^* \setminus I_R^*} \delta_{ij}^\gamma \Delta x_\gamma, \quad (i, j) \in U_R, \\ \Delta x_i &= \sum_{(\tau, \rho) \in U \setminus U_R} \delta_i^{\tau\rho} \Delta x_{\tau\rho} + \sum_{\gamma \in I^* \setminus I_R^*} \delta_i^\gamma \Delta x_\gamma, \quad i \in I_R^*. \end{aligned} \quad (13)$$

On the basis of (13) for the increment Δx we receive:

$$\sum_{(\tau, \rho) \in U \setminus U_R} \Lambda_{\tau\rho}^p \Delta x_{\tau\rho} + \sum_{\gamma \in I^* \setminus I_R^*} \Lambda_\gamma \Delta x_\gamma = 0, \quad p = \overline{1, q}, \quad (14)$$

Let us write down (13), (14) in a matrix form:

$$\Delta x_R = S_W \Delta x_W + S_N \Delta x_N; \quad \Delta_W \Delta x_W = -\Delta_N \Delta x_N, \quad (15)$$

where

$$\begin{aligned} \Delta x_W &= \{\Delta x_{ij}, (i, j) \in U_W; \Delta x_i, i \in I_W^*\}, \\ \Delta x_R &= (\Delta x_{ij}, (i, j) \in U_R; \Delta x_i, i \in I_R^*), \\ \Delta x_N &= \{\Delta x_{ij}, (i, j) \in U_N; \Delta x_i, i \in I_N^*\}, \\ U_K &= U_R \cup U_W, I_K^* = I_R^* \cup I_W^*, \\ U_N &= U \setminus U_K, I_N^* = I^* \setminus I_K^*, \\ S_W &= (\delta_{\tau\rho}, (\tau, \rho) \in U_W; \delta_\gamma, \gamma \in I_W^*), \\ S_N &= (\delta_{\tau\rho}, (\tau, \rho) \in U_N; \delta_\gamma, \gamma \in I_N^*). \end{aligned}$$

Matrices Δ_W and Δ_N consist of determinants of the structures generated by components of sets $W = \{U_W, I_W^*\}$, $N = \{U_N, I_N^*\}$ respectively. Set $W = \{U_W, I_W^*\}$ on the basis of which components of the vector Δx_W are constructed, is chosen so that $|\Delta_W| \neq 0$. As K is a support, from Theorem 4, then $|\Delta_W| \neq 0$. Hence, from (15) vector Δx_W is calculated (according to (16)):

$$\Delta x_W = -\Delta_W^{-1} \Delta_N \Delta x_N \quad (16)$$

Let us calculate the increment of objective function (1):

$$\Delta\varphi(x) = \sum_{(ij) \in U} c_{ij} \Delta x_{ij} = \sum_{(\tau, \rho) \in U \setminus U_R} \Delta_{\tau\rho} \Delta x_{\tau\rho} + \sum_{\gamma \in I^* \setminus I_R^*} \Delta_{\gamma} \Delta x_{\gamma},$$

using analytical expressions (13) for components of vector Δx_R .

$$\text{Let } r' = \Delta'_W \Lambda_W^{-1}, \quad r = (r_1, r_2, \dots, r_q),$$

$$\tilde{\Delta}_N = (\tilde{\Delta}_{\tau\rho}, (\tau, \rho) \in U_N; \tilde{\Delta}_{\gamma}, \gamma \in I_N^*),$$

$$\tilde{\Delta}_{\tau\rho} = \Delta_{\tau\rho} - \sum_{p=1}^q r_p \Lambda_{\tau\rho}^p, \quad (\tau, \rho) \in U_N,$$

$$\tilde{\Delta}_{\gamma} = \Delta_{\gamma} - \sum_{p=1}^q r_p \Lambda_{\gamma}^p, \quad \gamma \in I_N^*.$$

We shall name components of vector $\tilde{\Delta}_N = (\tilde{\Delta}_{\tau\rho}, (\tau, \rho) \in U_N; \tilde{\Delta}_{\gamma}, \gamma \in I_N^*)$ estimations. On construction, $\tilde{\Delta}_K = 0$, $K = \{U_K, I_K^*\}$. So, the increment of objective function (1) of problem (1)-(5) looks like

$$\Delta\varphi(x) = \sum_{(\tau, \rho) \in U_N} \tilde{\Delta}_{\tau\rho} \Delta x_{\tau\rho} + \sum_{\gamma \in I_N^*} \tilde{\Delta}_{\gamma} \Delta x_{\gamma}. \quad (17)$$

7. Optimality Criterion. An Estimation of Suboptimality

Theorem 5. *For optimality of plan x it is necessary and enough that there exists such a support $K = \{U_K, I_K^*\}$ of network G for system (2)-(3) at which on the support plan $\{x, K\}$ the following conditions of minimum are satisfied*

$$\begin{aligned} \tilde{\Delta}_{ij} x_{ij} &= \min_{0 \leq \omega \leq d_{ij}} \tilde{\Delta}_{ij} \omega, \quad (i, j) \in U_N, \\ \tilde{\Delta}_i x_i &= \min_{a_{*i} \leq v \leq a_i^*} \tilde{\Delta}_i v, \quad i \in I_N^*. \end{aligned} \quad (18)$$

The support on which the criterion of optimality (18) is carried out, is called optimal. The support is referred to as regular, if

$$\tilde{\Delta}_{ij} \neq 0, \quad (i, j) \in U_N, \quad \tilde{\Delta}_i \neq 0, \quad i \in I_N^*.$$

Consider formula (17) for the increment of the objective function:

$$\begin{aligned} \Delta\varphi(x) &= \sum_{(i,j) \in U_N} \tilde{\Delta}_{ij} \Delta x_{ij} + \sum_{i \in I_N^*} \tilde{\Delta}_i \Delta x_i \\ &= \sum_{(i,j) \in U_N} \tilde{\Delta}_{ij} (\bar{x}_{ij} - x_{ij}) + \sum_{i \in I_N^*} \tilde{\Delta}_i (\bar{x}_i - x_i). \end{aligned}$$

Let us find the maximal decrease of the objective function:

$$\Delta\varphi(x) = \sum_{(i,j) \in U_N} \tilde{\Delta}_{ij}(\bar{x}_{ij} - x_{ij}) + \sum_{i \in I_N^*} \tilde{\Delta}_i(\bar{x}_i - x_i)$$

on the variables $\bar{x}_{ij}, (i, j) \in U_N, \bar{x}_i, i \in I_N^*$ satisfying the following restrictions:

$$0 \leq \bar{x}_{ij} \leq d_{ij}, \quad (i, j) \in U_N; \quad a_{*i} \leq \bar{x}_i \leq a_i^*, \quad i \in I_N^*. \quad (19)$$

We shall designate this minimum as follows $\beta(x, K) = \min \Delta\varphi(x)$ and name it an estimation of suboptimality (ε -optimality) [2], [1] of the support plan $\{x, K\}$:

$$\begin{aligned} \beta(x, K) &= \min_{(19)} \Delta\varphi(x) = \sum_{\substack{(i,j) \in U_N, \\ (19), \tilde{\Delta}_{ij} < 0}} \tilde{\Delta}_{ij}(\bar{x}_{ij} - x_{ij}) \\ &+ \sum_{\substack{(i,j) \in U_N, \\ (19), \tilde{\Delta}_{ij} > 0}} \tilde{\Delta}_{ij}(\bar{x}_{ij} - x_{ij}) + \sum_{\substack{i \in I_N^*, \\ (19), \tilde{\Delta}_i < 0}} \tilde{\Delta}_i(\bar{x}_i - x_i) + \sum_{\substack{i \in I_N^*, \\ (19), \tilde{\Delta}_i > 0}} \tilde{\Delta}_i(\bar{x}_i - x_i) \\ &= \sum_{(i,j) \in U_N, (19)} \tilde{\Delta}_{ij}(z_{ij} - x_{ij}) + \sum_{i \in I_N^*, (19)} \tilde{\Delta}_i(z_i - x_i) = c'z - c'x. \end{aligned}$$

The solution of the problem of minimization of $\Delta\varphi(x)$ under conditions (19) is a pseudo-plan $z = (z_{ij}, (i, j) \in U; z_i, i \in I^*)$ of problem (1)-(5). Components of vector z are calculated by rules: on arcs $(i, j) \in U_N$ and nodes $i \in I_N^*$ from the following conditions of the optimality criterion:

$$\begin{aligned} z_{ij} &= 0, \quad \text{if } \tilde{\Delta}_{ij} > 0; & z_i &= a_{*i}, \quad \text{if } \tilde{\Delta}_i > 0; \\ z_{ij} &= d_{ij}, \quad \text{if } \tilde{\Delta}_{ij} < 0; & z_i &= a_i^* \quad \text{if } \tilde{\Delta}_i > 0; \\ z_{ij} &\in [0, d_{ij}], \quad \text{if } \tilde{\Delta}_{ij} = 0; (i, j) \in U_N; & z_i &\in [a_{*i}, a_i^*], \quad \text{if } \tilde{\Delta}_i = 0, i \in I_N. \end{aligned}$$

The components of vector $z_W = (z_{\tau\rho}, (\tau, \rho) \in U_W; z_\gamma, \gamma \in I_W^*)$ are calculated from the system

$$\begin{aligned} \Lambda_W z_W &= \bar{\beta}, \quad \bar{\beta} = (\bar{\beta}^p, p = \overline{1, q}), \\ \bar{\beta}^p &= \bar{\alpha}^p - \sum_{(\tau, \rho) \in U_N} \Lambda_{\tau\rho}^p z_{\tau\rho} - \sum_{\gamma \in I_N^*} \Lambda_\gamma^p z_\gamma, \\ \bar{\alpha}^p &= \beta^p - \sum_{(i,j) \in U_R} \lambda_{ij}^p \tilde{x}_{ij} - \sum_{i \in I_R^*} \lambda_i^p \tilde{x}_i. \end{aligned}$$

The components $z_R = (z_{\tau\rho}, (\tau, \rho) \in U_R; z_\gamma, \gamma \in I_R^*)$ are calculated from the system:

$$z_{ij} = \sum_{(\tau, \rho) \in U \setminus U_R} z_{\tau\rho} \delta_{ij}^{\tau\rho} + \sum_{\gamma \in I^* \setminus I_R^*} z_\gamma \delta_{ij}^\gamma + \tilde{z}_{ij}, \quad (i, j) \in U_R,$$

$$z_i = \sum_{(\tau, \rho) \in U \setminus U_R} z_{\tau\rho} \delta_i^{\tau\rho} + \sum_{\gamma \in I^* \setminus I_R^*} z_\gamma \delta_i^\gamma + \tilde{z}_i, \quad i \in I_R^*,$$

where $\tilde{z} = (\tilde{z}_{ij}, (i, j) \in U; \tilde{z}_i, i \in I^*)$ – any particular solution of the network part (1.2) of system (2), (3) for the conjugate flow \tilde{z} .

Theorem 6. (ε -Optimality Criterion) *At any $\varepsilon \geq 0$ for ε – optimality of plan x it is necessary and enough that a support K exists, at which $\beta(x, K) \leq \varepsilon$.*

As shown in [5], the estimation of suboptimality allows the following decomposition $\beta(x, K) = \mu(x) + \mu(K)$, where $\mu(x) = \varphi(x) - \varphi(x^0)$ – a measure for nonoptimality of plan x , $\mu(K) = \psi(\lambda^0) - \psi(\lambda)$ – a measure for nonoptimality of the support. Thus, it is possible to improve an estimation of ε – optimality by means of independent improvement of the flow and the support. We will do the improvement of the support with the help of the dual support method.

8. The Dual Problem. Decomposition of the Linear System for Calculation of the Conjugate Flow

The dual problem for problem (1)-(5) looks like:

$$\begin{aligned} \sum_{i \in I \setminus I^*} a_i y_i + \sum_{p=1}^q \beta^p \tau_p + \sum_{i \in I^*} a_{*i} \omega_i - \sum_{i \in I^*} a_i^* t_i - \sum_{(i,j) \in U} d_{ij} v_{ij} &\longrightarrow \max, \\ y_i - \mu_{ij} y_j - v_{ij} + \sum_{p=1}^q \lambda_{ij}^p \tau_p &\leq c_{ij}, \quad (i, j) \in U, \\ -y_i \text{sign}(i) + \omega_i - t_i + \sum_{p=1}^q \lambda_i^p \tau_p &= c_i, \quad i \in I^*, \\ v_{ij} &\geq 0, \quad (i, j) \in U, \\ t_i &\geq 0, \quad \omega_i \geq 0, \quad i \in I^*. \end{aligned} \tag{20}$$

A vector

$$\lambda = (y, \tau, t, \omega, v) = (y_i, i \in I; \tau_k, k = \overline{1, q}; t_i, \omega_i, i \in I^*; v_{ij}, (i, j) \in U),$$

which components satisfy all restrictions of dual problem (20), is referred to as a dual plan of problem (1)-(5). We shall calculate the conjugate flow $\delta = (\delta_{ij}, (i, j) \in U; \delta_i, i \in I^*)$ corresponding to the dual plan λ by:

$$\delta_{ij} = c_{ij} - y_i + \mu_{ij} y_j - \sum_{p=1}^q \lambda_{ij}^p \tau_p \leq c_{ij}, \quad (i, j) \in U,$$

$$\delta_i = c_i + y_i \text{sign}(i) - \sum_{p=1}^q \lambda_i^p \tau_p, \quad i \in I^*.$$

If for the support non degenerate [1] conjugate flow $\{\delta, K\}$ support K is not optimum, then in case of dual nondegeneracy [1] there exists a variation $\Delta\delta$ of conjugate flow δ , which conducts to an increase in the dual objective function. Two variants for construction of a direction are possible.

1) Let (i_0, j_0) – an arc on which the limit of flow \bar{x}_{ij} (0 or $d_{i_0j_0}$) is achieved. We shall construct a direction $\Delta\delta_K = (\Delta\delta_{ij}, (i, j) \in U_K; \Delta\delta_i, i \in I_K^*)$ as follows:

$$\begin{aligned} \Delta\delta_{i_0j_0} &= \begin{cases} -1, & \text{if } \bar{x}_{i_0j_0} = d_{i_0j_0}, \\ 1, & \text{if } \bar{x}_{i_0j_0} = 0, \end{cases} \\ \Delta\delta_{ij} &= 0, \quad (i, j) \in U_K \setminus (i_0, j_0), \\ \Delta\delta_i &= 0, \quad i \in I_K^*. \end{aligned}$$

2) Let i_0 – is a dynamic node on which the limit of component $\bar{x}_{i_0}(\bar{x}_{i_0} = b_{*i_0} \vee b_{i_0}^*)$ is achieved.

We shall construct a direction $\Delta\delta_K = (\Delta\delta_{ij}, (i, j) \in U_K; \Delta\delta_i, i \in I_K^*)$ as follows:

$$\begin{aligned} \Delta\delta_{i_0} &= \begin{cases} -1, & \text{if } \bar{x}_{i_0} = b_{i_0}^*, \\ 1, & \text{if } \bar{x}_{i_0} = b_{*i_0}, \end{cases} \\ \Delta\delta_{ij} &= 0, \quad (i, j) \in U_K, \quad \Delta\delta_i = 0, \quad i \in I_K^* \setminus i_0. \end{aligned}$$

Arc (i_0, j_0) and dynamic node i_0 are named critical.

Let us consider case 1). We shall designate $\alpha = \Delta\delta_{i_0j_0}$, $\tau_p = r_p$, $p = \overline{1, q}$; $y_i = u_i$, $i \in I$. Support elements of an increment of the conjugate flow satisfy the system:

$$\begin{aligned} \Delta\delta_{i_0j_0} &= -(\Delta u_{i_0} - \mu_{i_0j_0} \Delta u_{j_0} + \sum_{p=1}^q \lambda_{ij}^p \Delta r_p) = \alpha, \\ \Delta\delta_{ij} &= -(\Delta u_i - \mu_{ij} \Delta u_j + \sum_{p=1}^q \lambda_{ij}^p \Delta r_p) = 0, \quad (i, j) \in U_K \setminus (i_0, j_0), \quad (21) \\ \Delta\delta_i &= \Delta u_i \text{sign}(i) - \sum_{p=1}^q \lambda_i^p \Delta r_p = 0, \quad i \in I_K^*. \end{aligned}$$

Let us consider any element (arc or node) from set $W = (U_W, I_W^*)$. To each element from set of sets W there corresponds the characteristic vector $\delta(\tau, \rho) \vee \delta(\gamma)$ generated by this element. We multiply each nonzero element of the characteristic vector $\delta(\tau, \rho)$, $(\tau, \rho) \in U_W$ by the equation of system (21),

corresponding to this element, and we sum up the received equalities:

$$\sum_{p=1}^q \Lambda_{\tau\rho}^p \Delta r_p = -\alpha \delta_{i_0 j_0}^{\tau\rho}, (\tau, \rho) \in U_W. \quad (22)$$

Consider set I_W^* . To each element $\gamma \in I_W^*$ there corresponds a characteristic vector $\delta(\gamma) = (\delta_{ij}^\gamma, (i, j) \in U; \delta_i^\gamma, i \in I^*)$. We multiply every nonzero component of vector $\delta(\gamma)$ by corresponding to this component equation of system (21). We execute the specified transformations for all elements of set I_W^* :

$$\sum_{p=1}^q \Lambda_\gamma^p \Delta r_p = -\alpha \delta_{i_0 j_0}^\gamma, \gamma \in I_W^*. \quad (23)$$

In a matrix-vector form relations (22), (23) will become:

$$\Lambda'_W \Delta r = \bar{\alpha}, \bar{\alpha} = (-\alpha \delta_{i_0 j_0}^{\tau\rho}, (\tau, \rho) \in U_W; -\alpha \delta_{i_0 j_0}^\gamma, \gamma \in I_W^*). \quad (24)$$

The aggregation of sets $K = \{U_K, I_K^*\}$ is a support of network $G = (I, U)$ for system (2), (3) and hence, matrix Λ_W is nonsingular.

We shall calculate vector δr :

$$\delta r = (\Lambda'_W)^{-1} \bar{\alpha}. \quad (25)$$

Components $\Delta \delta_N = (\Delta \delta_{\tau\rho}, (\tau, \rho) \in U_N; \Delta \delta_\gamma, \gamma \in I_N^*)$ of direction $\Delta \delta$ are:

$$\Delta \delta_{\tau\rho} = \begin{cases} -\sum_{p=1}^q \Lambda_{\tau\rho}^p \Delta r_p - \Delta \delta_{i_0 j_0} \delta_{i_0 j_0}^{\tau\rho}, & \text{if } (i_0, j_0) - \text{critical arc;} \\ -\sum_{p=1}^q \Lambda_{\tau\rho}^p \Delta r_p - \Delta \delta_{i_0} \delta_{i_0}^{\tau\rho}, & \text{if } i_0 - \text{critical node;} \end{cases}$$

$$\Delta \delta_\gamma = \begin{cases} -\sum_{p=1}^q \Lambda_{\tau\rho}^p \Delta r_p - \Delta \delta_{i_0 j_0} \delta_{i_0 j_0}^\gamma, & \text{if } (i_0, j_0) - \text{critical arc;} \\ -\sum_{p=1}^q \Lambda_\gamma^p \Delta r_p - \Delta \delta_{i_0} \delta_{i_0}^\gamma, & \text{if } i_0 - \text{critical node.} \end{cases}$$

In a matrix-vector form last relations look like

$$\Delta \delta_N = -\Lambda'_N \Delta r - \alpha t,$$

where vector $t = (\delta_{i_0 j_0}^{\tau\rho}, (\tau, \rho) \in U_N; \delta_{i_0 j_0}^\gamma, \gamma \in I_N^*)$ if arc (i_0, j_0) is critical, and $t = (\delta_{i_0}^{\tau\rho}, (\tau, \rho) \in U_N; \delta_{i_0}^\gamma, \gamma \in I_N^*)$, if dynamic node i_0 is critical. The dual step along the constructed direction $\Delta \delta$ is calculated by standard rules [2], [1].

References

- [1] V.V. Al'sevitch, R. Gabasov, V.S. Glushenkov, *Optimization of Linear Economical Models: Static Problems*, Minsk, BSU (2000), In Russian.
- [2] R. Gabasov, F.M. Kirillova, *Methods of Linear Programming. Part 3. Special Problems*, Minsk, BSU (1980), In Russian.

- [3] D. Ivanchev, *Network Optimization*, Heron Press, Sofia (2002), In Bulgarian.
- [4] V.M. Kotov, L.A. Pilipchuk, E.P. Sobolevskaya, *Theory of Algorithms*, Part 1, Minsk, BSU (2001), In Russian.
- [5] L.A. Pilipchuk, Algorithms for solution of a nonhomogeneous network distributive problem, *News of Byelorussian Academy of Sciences*, No. 3 (1986), In Russian.
- [6] L.A. Pilipchuk, Algorithms for solution of large sparse linear systems in extremal distributive problems, In: *Proceedings of the I International Conference "Information Systems and Technologies" (IST'2002)*, Minsk (2002), In Russian.
- [7] L.A. Pilipchuk, *Network Optimization Problems Applications of Mathematics in Engineering and Economics'27* (Ed-s: D. Ivanchev, M.D. Todorov), Heron Press, Sofia (2002).
- [8] L.A. Pilipchuk, Y.V. Malakhouskaya, D.R. Kincaid, M. Lai, Algorithms of solving large sparse underdetermined linear systems with embedded network structure, *East-West J. of Mathematics*, **4**, No. 2 (2002), 191-202.
- [9] L.A. Pilipchuk, Y.H. Pesheva, Decomposition of linear system in dual flow problems, *Mathematica Balkanica*, New Series, **21**, No-s: 1-2 (2007), 21-29.
- [10] L.A. Pilipchuk, A.S. Pilipchuk, Optimality criterion for one dual linear extreme problem, *Vestnik BSU*, **1**, No. 2 (1998), In Russian.
- [11] L.A. Pilipchuk, E.S. Vecharynski, Y.H. Pesheva, Solution of large linear systems with embedded network structure for a non-homogeneous network flow programming problem, *Mathematica Balkanica*, New Series, **22**, No-s. 3-4 (2008), 235-254.

